

YORK® ABSORPTION CHILLERS AND HEAT PUMP

WITH INNOVATIVE 2-STEP EVAPORATION AND ABSORPTION-CYCLE TECHNOLOGY

DRIVING HEAT SOURCE	MODEL AND DESCRIPTION	
HOT WATER	Single Effect Hot Water Model: YHAU-CL/CH Capacity: 105 - 7,034 kW / 30 - 2,000 TR Application: Combined heat and power (CHP), commercial cooling, industrial process cooling	
LOW TEMPERATURE HOT WATER	Single Effect Double Lift Hot Water Model: YHAU-CL-DXS Capacity: 176 - 4,395 kW / 50 - 1,250 TR Application: Combined heat and power (CHP), commercial cooling, industrial process cooling	
LOW PRESSURE STEAM	Single Effect Steam Model: YHAU-C Capacity: 105 - 7,034 kW / 30 - 2,000 TR Application: Combined heat and power (CHP), commercial cooling, industrial process cooling	
MEDIUM PRESSURE STEAM	Double Effect Steam Model: YHAU-CW Capacity: 422 - 14,067 kW / 120 - 4,000 TR Application: Combined heat and power (CHP), commercial cooling, industrial process cooling	
DIRECT FIRED	Small Double Effect Natural Gas or Light Oil* Model: YHAU-CG/CA-CXR Capacity: 105 - 352 kW / 30 - 100 TR Application: Commercial cooling	
DIRECT FIRED	Large Double Effect Natural Gas or Light Oil Model: YHAU-CG/CA Capacity: 422 - 5,626 kW / 120 - 1,600 TR Application: Commercial cooling, industrial process cooling	

*Utilizes standard cycle

DRIVING HEAT SOURCE	MODEL AND DESCRIPTION	
EXHAUST GAS	Double Effect Exhaust Gas Model: YHAU-CE Capacity: 527 - 5,064 kW / 150 - 1,440 TR Application: Combined heat and power (CHP), commercial cooling	
EXHAUST GAS AND LOW TEMPERATURE HOT WATER	Multi Energy Exhaust and Jacket Hot Water Model: YHAU-CE -J Capacity: 527 - 5,064 kW / 150 - 1,440 TR Application: Combined heat and power (CHP), commercial cooling	
EXHAUST GAS AND LOW TEMPERATURE HOT WATER AND DIRECT FIRED	Multi Energy Exhaust, Jacket Hot Water, Direct Fired Model: YHAU-CGE-J Capacity: Custom Application: Combined heat and power (CHP), commercial cooling	
NATURAL GAS AND LOW TEMPERATURE HOT WATER	Gas Gene-Link Model: YHAU-CG-J Capacity: 422 - 5,626 kW / 120 - 1,600 TR Application: Combined heat and power (CHP), commercial cooling	
MEDIUM PRESSURE STEAM AND LOW TEMPERATURE HOT WATER	Steam Gene-Link Model: YHAU-CW-J Capacity: 422 - 14,067 kW / 120 - 4,000 TR Application: Combined heat and power (CHP), industrial process cooling	
HOT WATER, STEAM, DIRECT FIRED	Low Leaving Chilled Water Temperature (Down to -5°C) Model: YHAU-C-LL Capacity: 176 - 1,758 kW / 50 - 500 TR Application: Industrial process cooling / refrigeration	
HOT WATER, STEAM, DIRECT FIRED	Absorption Heat Pump (Up to 90°C) Model: YHAP Capacity: Custom Application: District heating, industrial process heating	



Johnson Controls, the Johnson Controls logo, YORK and Metasys are registered trademarks of Johnson Controls, Inc. in the United States of America and other countries. Other trademarks used herein may be trademarks or registered trademarks of other companies.
 © 2017 Johnson Controls, Inc. P.O. Box 423, Milwaukee, WI 53201. All rights reserved worldwide. Printed in USA. PUBL-8697-A-0717.

FOR MORE INFORMATION CONTACT JOHNSONCONTROLS.COM

